NSN 5320-01-315-9288

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Thread Direction:

Fastener Length:

Identification Code Color:

Between 0.760 inches and 0.780 inches

За

Blue



View Online at https://aerobasegroup.com/nsn/5320-01-315-9288

Head Style:
Flush countersunk
Width Between Flats:
Between 0.0947 inches and 0.0967 inches
Shank Diameter:
Between 0.2641 inches and 0.2651 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.5018 inches and 0.5066 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
Between 0.370 inches and 0.380 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Thread Size:
0.250 inches
Shear Strength:
10490 double pounds per square inch
Countersink Angle:
100.0 degrees
Material:
Titanium alloy uns r54520
Material Specification:
Ams4967 mfr ref single material response
Thread Series Designator:
Unjf
Specification Data:
73197-hl113vf-8-6 manufacturers standard
Shelf Life:
N/a

NSN 5320-01-315-9288

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0