## NSN 5320-01-317-4065

Tubular Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-317-4065

View Online at https://aerobasegroup.com/nsn/5320-01-317-4065
Fastener Length:
Between 0.086 inches and 0.092 inches
Head Style:
Flat fillister
Head Height:
0.020 inches
Hole Diameter:
Between 0.098 inches and 0.101 inches
Shank Diameter:
Between 0.122 inches and 0.128 inches
Shank Style:
Tubular
Head Major Diameter:
0.250 inches
Hole Depth:
0.065 inches
Criticality Code Justification:
Zzzy
Special Features:
tem must comply with requirements of defense supply center philadelphia production standard po0294nrp
Material:
Steel comp 303
Material Specification:
Astm a581 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mi5-28, cagec 94271 mfr ref single treatment response
Test Data Document:
31349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Departure From Cited Document:
As modified by material and locking feature as applicable
Reference Number Differentiating Characteristics:
Areference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing
and testing specifications available at the dla icp
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: