NSN 5320-01-317-6770

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Thread Direction:

За



View Online at https://aerobasegroup.com/nsn/5320-01-317-6770

Identification Code Color:
Blue
Fastener Length:
Between 0.627 inches and 0.647 inches
Head Style:
Flush countersunk
Width Between Flats:
Between 0.0791 inches and 0.0806 inches
Shank Diameter:
Between 0.1885 inches and 0.1895 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.2966 inches and 0.3016 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
Between 0.307 inches and 0.317 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
Min. Tensile Strength (psi): 95000 pounds per square inch
95000 pounds per square inch
95000 pounds per square inch Thread Size:
95000 pounds per square inch Thread Size: 0.190 inches
95000 pounds per square inch Thread Size: 0.190 inches Shear Strength:
95000 pounds per square inch Thread Size: 0.190 inches Shear Strength: 5380 double pounds per square inch
95000 pounds per square inch Thread Size: 0.190 inches Shear Strength: 5380 double pounds per square inch Countersink Angle:
95000 pounds per square inch Thread Size: 0.190 inches Shear Strength: 5380 double pounds per square inch Countersink Angle: 100.0 degrees
95000 pounds per square inch Thread Size: 0.190 inches Shear Strength: 5380 double pounds per square inch Countersink Angle: 100.0 degrees Material:
95000 pounds per square inch Thread Size: 0.190 inches Shear Strength: 5380 double pounds per square inch Countersink Angle: 100.0 degrees Material: Titanium alloy uns r54520
95000 pounds per square inch Thread Size: 0.190 inches Shear Strength: 5380 double pounds per square inch Countersink Angle: 100.0 degrees Material: Titanium alloy uns r54520 Material Specification:
95000 pounds per square inch Thread Size: 0.190 inches Shear Strength: 5380 double pounds per square inch Countersink Angle: 100.0 degrees Material: Titanium alloy uns r54520 Material Specification: Ams4967 mfr ref single material response
95000 pounds per square inch Thread Size: 0.190 inches Shear Strength: 5380 double pounds per square inch Countersink Angle: 100.0 degrees Material: Titanium alloy uns r54520 Material Specification: Ams4967 mfr ref single material response Thread Series Designator:
95000 pounds per square inch Thread Size: 0.190 inches Shear Strength: 5380 double pounds per square inch Countersink Angle: 100.0 degrees Material: Titanium alloy uns r54520 Material Specification: Ams4967 mfr ref single material response Thread Series Designator: Unjf
95000 pounds per square inch Thread Size: 0.190 inches Shear Strength: 5380 double pounds per square inch Countersink Angle: 100.0 degrees Material: Titanium alloy uns r54520 Material Specification: Ams4967 mfr ref single material response Thread Series Designator: Unjf Specification Data:
95000 pounds per square inch Thread Size: 0.190 inches Shear Strength: 5380 double pounds per square inch Countersink Angle: 100.0 degrees Material: Titanium alloy uns r54520 Material Specification: Ams4967 mfr ref single material response Thread Series Designator: Unjf Specification Data: 73197-hl11vf-6-5 manufacturers standard
95000 pounds per square inch Thread Size: 0.190 inches Shear Strength: 5380 double pounds per square inch Countersink Angle: 100.0 degrees Material: Titanium alloy uns r54520 Material Specification: Ams4967 mfr ref single material response Thread Series Designator: Unjf Specification Data: 73197-hl11vf-6-5 manufacturers standard Shelf Life:

NSN 5320-01-317-6770

Pin-rivet - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0