NSN 5320-01-318-2025

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-318-2025

| Thread Class: |
|--|
| 3b |
| Thread Direction: |
| Right-hand |
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.527 inches and 0.530 inches |
| Shank Style: |
| Blind rivet, nut and bolt (assembly) |
| Head Major Diameter: |
| Between 0.585 inches and 0.590 inches |
| Expansion Device: |
| Threaded mandrel |
| Lubrication: |
| Dry film |
| Grip Length: |
| 0.906 inches |
| Thready Qty Per Inch (tpi): |
| 24 |
| Thread Size: |
| 0.375 inches |
| Countersink Angle: |
| 100.0 degrees |
| Special Features: |
| Furnished without bolt |
| Material: |
| Steel comp xm-13 expander |
| Material Specification: |
| Qq-s-763, cond a federal specification single material response sleeve |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |