
## NSN 5320-01-318-9621

Pin-rivet - Page 1 of 2



Thread Class:

3a

**Thread Direction:** 

Right-hand

## Fastener Length:

Between 1.455 inches and 1.475 inches

### Head Style:

Err-090

#### Head Height:

Between 0.130 inches and 0.140 inches

## Width Between Flats:

Between 0.1582 inches and 0.1617 inches

## Shank Diameter:

Between 0.3640 inches and 0.3680 inches

#### Shank Style:

## Head Major Diameter:

Between 0.585 inches and 0.620 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

Between 0.870 inches and 0.885 inches

## Thready Qty Per Inch (tpi):

24

## Min. Tensile Strength (psi):

180000 pounds per square inch

### Thread Size:

0.375 inches

#### Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740

#### **Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military

specification 3rd material response

#### Surface Treatment:

Cadmium and chromate

#### Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

#### **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:



# NSN 5320-01-318-9621

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.

