## NSN 5320-01-319-2156

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-319-2156 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.073 inches and 2.093 inches **Head Style:** Err-090 **Head Height:** Between 0.080 inches and 0.090 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style: Head Major Diameter:** Between 0.387 inches and 0.412 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 1.683 inches and 1.698 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 180000 pounds per square inch **Thread Size:** 0.250 inches Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response

--

Unjf

N/a

Shelf Life:

**Unit Of Measure:** 

**Thread Series Designator:** 

## NSN 5320-01-319-2156

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.