
# NSN 5320-01-319-8721

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

### Fastener Length:

Between 1.072 inches and 1.092 inches

#### Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2490 inches and 0.2495 inches

Shank Style:

#### Head Major Diameter:

Between 0.5018 inches and 0.5066 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

Between 0.677 inches and 0.697 inches

### Thready Qty Per Inch (tpi):

28

### Min. Tensile Strength (psi):

160000 pounds per square inch

#### **Thread Size:**

0.250 inches

#### Shear Strength:

95000 single pounds per square inch

#### Countersink Angle:

100.0 degrees

#### Material:

Titanium alloy uns r56400

#### Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Thread Series Designator:

Unjf

# Shelf Life:

N/a

### Unit Of Measure:

--

### Demilitarization:

No

# NSN 5320-01-319-8721

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

