# NSN 5320-01-319-9959

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-319-9959



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 0.802 inches and 0.822 inches

#### Head Style:

Err-090

#### **Head Height:**

Between 0.102 inches and 0.112 inches

#### Width Between Flats:

Between 0.1270 inches and 0.1295 inches

#### Shank Diameter:

Between 0.3115 inches and 0.3120 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.475 inches and 0.505 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

Between 0.307 inches and 0.317 inches

#### Thready Qty Per Inch (tpi):

24

#### Min. Tensile Strength (psi):

160000 pounds per square inch

## Thread Size:

0.312 inches

## Shear Strength:

95000 single pounds per square inch

#### Material:

Titanium alloy uns r56400

#### Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Thread Series Designator:

Unjf

# Shelf Life:

N/a

# Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-01-319-9959

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

