NSN 5320-01-320-4049

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-320-4049 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** Between 1.428 inches and 1.448 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3115 inches and 0.3120 inches **Shank Style: Head Major Diameter:** Between 0.6287 inches and 0.6335 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.933 inches and 0.943 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.312 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5320-01-320-4049

Pin-rivet - Page 2 of 2



Fiig:

A528u0