# NSN 5320-01-320-4536

Pin-rivet - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5320-01-320-4536

#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.502 inches and 0.522 inches

#### Head Style:

Err-090

#### **Head Height:**

Between 0.045 inches and 0.047 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.1890 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.296 inches and 0.301 inches

#### Grip Length:

Between 0.182 inches and 0.197 inches

## Thready Qty Per Inch (tpi):

32

#### Thread Size:

0.190 inches

#### **Special Features:**

Hi-kote 1 per hi-shear spec. 294 and cetyl alcohol lube per hi-shear spec. 305

#### Material:

Titanium alloy

#### **Material Specification:**

Ams4928 assn standard single material response or ams4967 assn standard single material response

#### Thread Series Designator:

Unjf

# Specification Data:

73197-hlt411a+6-3 professional/industrial association specification

## Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A528u0

