
# NSN 5320-01-320-4543

Pin-rivet - Page 1 of 1



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.675 inches and 1.695 inches

#### Head Style:

Err-090

#### **Head Height:**

Between 0.104 inches and 0.107 inches

#### Width Between Flats:

Between 0.2207 inches and 0.2242 inches

#### Shank Diameter:

Between 0.4990 inches and 0.4995 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.7480 inches and 0.7540 inches

#### Grip Length:

Between 0.995 inches and 1.010 inches

#### Thready Qty Per Inch (tpi):

20

#### Thread Size:

0.500 inches

#### **Special Features:**

Hi-kote 1 per hi-shear spec. 294 and cetyl alcohol lube per hi-shear spec. 305

#### Material:

Titanium alloy

#### **Material Specification:**

Ams4928 assn standard single material response or ams4967 assn standard single material response

#### Thread Series Designator:

Unjf

## **Specification Data:**

73197-hlt41116-16 professional/industrial association specification

## Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A528u0

