# NSN 5320-01-320-4544

Pin-rivet - Page 1 of 1





## Thread Class:

3a

**Thread Direction:** 

Right-hand

## Fastener Length:

Between 0.885 inches and 0.905 inches

## Head Style:

Err-090

#### **Head Height:**

Between 0.059 inches and 0.069 inches

## Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2490 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.387 inches and 0.412 inches

## Grip Length:

Between 0.495 inches and 0.510 inches

## Thready Qty Per Inch (tpi):

28

## Thread Size:

0.250 inches

## **Special Features:**

Hi-kote 1 per hi-shear spec. 294 and cetyl alcohol lube per hi-shear spec. 305

## Material:

Titanium alloy

## **Material Specification:**

Ams4928 assn standard single material response or ams4967 assn standard single material response

## Thread Series Designator:

Unjf

# **Specification Data:**

73197-hlt410a+8-8 professional/industrial association specification

# Shelf Life:

N/a

# Unit Of Measure:

---

#### **Demilitarization:**

No

Fiig:

A528u0