NSN 5320-01-320-4974

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-320-4974 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.490 inches and 0.510 inches **Head Style:** Err-090 **Head Height:** Between 0.055 inches and 0.065 inches Width Between Flats: Between 0.0791 inches and 0.0801 inches **Shank Diameter:** Between 0.1630 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.306 inches and 0.322 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** W/s: aircraft, b-2 bomber (atb) **Grip Length:** Between 0.183 inches and 0.193 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.164 inches **Shear Strength:** 95000 single pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5320-01-320-4974

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0