## NSN 5320-01-320-6279

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-320-6279

Thread Class						
Thread Class:						
3a						
Thread Direction:						
Right-hand						
Identification Code Color:						
Blue						
Fastener Length:						
Between 0.753 inches and 0.773 inches						
Head Style:						
Err-090						
Head Height:						
Between 0.045 inches and 0.055 inches						
Width Between Flats:						
Between 0.0791 inches and 0.0806 inches						
Shank Diameter:						
Between 0.2016 inches and 0.2026 inches						
Shank Style:						
Pin-rivet, straight, threaded						
Head Major Diameter:						
Between 0.295 inches and 0.315 inches						
Lubrication:						
Cetyl alcohol, specification 305, hi-shear corp						
Grip Length:						
Between 0.433 inches and 0.443 inches						
Thready Qty Per Inch (tpi):						
32						
Min. Tensile Strength (psi):						
2500 pounds per square inch						
Thread Size:						
0.190 inches						
Shear Strength:						
6130 double pounds per square inch						
Material:						
Titanium alloy uns r54520						
Material Specification:						
Ams4967 mfr ref single material response						
Thread Series Designator:						
Unjf						
Specification Data:						
73197-hl110vf-6-7 manufacturers standard						
Shelf Life:						

N/a

## NSN 5320-01-320-6279

Pin-rivet - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A528u0