## NSN 5320-01-320-9946

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-320-9946 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.803 inches and 0.823 inches **Head Style:** Flush countersunk **Shank Diameter:** Between 0.311 inches and 0.312 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.469 inches and 0.474 inches **Tip Diameter:** Between 0.302 inches and 0.306 inches **Grip Length:** Between 0.308 inches and 0.318 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.312 inches **Shear Strength:** 125000 double pounds per square inch **Countersink Angle:** 100.0 degrees **Thread Tolerance Class:** 3a external Material: Steel **Material Specification:** Qq-s-763 type 431 federal specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type ii, cl 3, cetyl alchcl lube per hi-shear specification 305 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5320-01-320-9946

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0