## NSN 5320-01-320-9947

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-320-9947 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.635 inches and 0.655 inches **Head Style:** Flush countersunk **Shank Diameter:** Between 0.249 inches and 0.250 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.390 inches and 0.395 inches **Tip Diameter:** Between 0.241 inches and 0.244 inches **Grip Length:** Between 0.245 inches and 0.255 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Shear Strength:** 125000 double pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel **Material Specification:** Qq-s-736, t431 federal specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, tii, cl3, cetyl alcohol lube per hi-shear spec. 305 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5320-01-320-9947

Pin-rivet - Page 2 of 2



Fiig:

A528u0