

View Online at <https://aerobasegroup.com/nsn/5320-01-321-7825>

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 18.8 millimeters and 19.2 millimeters

**Head Style:**

Err-090

**Head Height:**

Between 0.95 millimeters and 1.20 millimeters

**Width Between Flats:**

Between 1.61 millimeters and 1.64 millimeters

**Shank Diameter:**

Between 4.478 millimeters and 4.490 millimeters

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 6.25 millimeters and 6.65 millimeters

**Grip Length:**

Between 9.9 millimeters and 10.1 millimeters

**Min. Tensile Strength (psi):**

18200 newtons per square millimeter

**Thread Size:**

6.0 millimeters

**Thread Pitch In Millimeters:**

1.000

**Shear Strength:**

43500 double newtons per square millimeter

**Thread Tolerance Class:**

4h external

**Material:**

Titanium alloy

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Thread Series Designator:**

Iso m

**Specification Data:**

73197-hl-310-04-10 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0