

View Online at <https://aerobasegroup.com/nsn/5320-01-321-7826>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Identification Code Color:**

Blue

**Fastener Length:**

Between 0.947 inches and 0.967 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.947 inches and 0.967 inches

**Shank Diameter:**

Between 0.2641 inches and 0.2651 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.3898 inches and 0.3948 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

Between 0.557 inches and 0.567 inches

**Thread Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

95000 pounds per square inch

**Thread Size:**

0.250 inches

**Shear Strength:**

10490 double pounds per square inch

**Countersink Angle:**

100.0 degrees

**Material:**

Titanium alloy uns r54520

**Material Specification:**

Ams4967 mfr ref single material response

**Thread Series Designator:**

Unjf

**Specification Data:**

73197-hl111vf-8-9 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0