NSN 5320-01-321-7826

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Thread Direction:

Fastener Length:

Identification Code Color:

Between 0.947 inches and 0.967 inches

За

Blue



View Online at https://aerobasegroup.com/nsn/5320-01-321-7826

Flush countersunk Width Between Flats: Between 0.947 inches and 0.967 inches Shank Diameter: Between 0.2641 inches and 0.2651 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.3898 inches and 0.3948 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp Grip Length: Between 0.557 inches and 0.567 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 95000 pounds per square inch Thread Size: 0.250 inches Shear Strength: 10490 double pounds per square inch Countersink Angle: 100.0 degrees Material: Titanium alloy uns r54520 Material Specification: Ams4967 mfr ref single material response
Between 0.947 inches and 0.967 inches Shank Diameter: Between 0.2641 inches and 0.2651 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.3898 inches and 0.3948 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp Grip Length: Between 0.557 inches and 0.567 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 95000 pounds per square inch Thread Size: 0.250 inches Shear Strength: 10490 double pounds per square inch Countersink Angle: 100.0 degrees Material: Titanium alloy uns r54520 Material Specification: Ams4967 mfr ref single material response
Shank Diameter: Between 0.2641 inches and 0.2651 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.3898 inches and 0.3948 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp Grip Length: Between 0.557 inches and 0.567 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 95000 pounds per square inch Thread Size: 0.250 inches Shear Strength: 10490 double pounds per square inch Countersink Angle: 100.0 degrees Material: Titanium alloy uns r54520 Material Specification: Ams4967 mfr ref single material response
Between 0.2641 inches and 0.2651 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.3898 inches and 0.3948 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp Grip Length: Between 0.557 inches and 0.567 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 95000 pounds per square inch Thread Size: 0.250 inches Shear Strength: 10490 double pounds per square inch Countersink Angle: 100.0 degrees Material: Titanium alloy uns r54520 Material Specification: Ams4967 mfr ref single material response
Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.3898 inches and 0.3948 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp Grip Length: Between 0.557 inches and 0.567 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 95000 pounds per square inch Thread Size: 0.250 inches Shear Strength: 10490 double pounds per square inch Countersink Angle: 100.0 degrees Material: Titanium alloy uns r54520 Material Specification: Ams4967 mfr ref single material response
Pin-rivet, straight, threaded Head Major Diameter: Between 0.3898 inches and 0.3948 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp Grip Length: Between 0.557 inches and 0.567 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 95000 pounds per square inch Thread Size: 0.250 inches Shear Strength: 10490 double pounds per square inch Countersink Angle: 100.0 degrees Material: Titanium alloy uns r54520 Material Specification: Ams4967 mfr ref single material response
Head Major Diameter: Between 0.3898 inches and 0.3948 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp Grip Length: Between 0.557 inches and 0.567 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 95000 pounds per square inch Thread Size: 0.250 inches Shear Strength: 10490 double pounds per square inch Countersink Angle: 100.0 degrees Material: Titanium alloy uns r54520 Material Specification: Ams4967 mfr ref single material response
Between 0.3898 inches and 0.3948 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp Grip Length: Between 0.557 inches and 0.567 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 95000 pounds per square inch Thread Size: 0.250 inches Shear Strength: 10490 double pounds per square inch Countersink Angle: 100.0 degrees Material: Titanium alloy uns r54520 Material Specification: Ams4967 mfr ref single material response
Lubrication: Cetyl alcohol, specification 305, hi-shear corp Grip Length: Between 0.557 inches and 0.567 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 95000 pounds per square inch Thread Size: 0.250 inches Shear Strength: 10490 double pounds per square inch Countersink Angle: 100.0 degrees Material: Titanium alloy uns r54520 Material Specification: Ams4967 mfr ref single material response
Cetyl alcohol, specification 305, hi-shear corp Grip Length: Between 0.557 inches and 0.567 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 95000 pounds per square inch Thread Size: 0.250 inches Shear Strength: 10490 double pounds per square inch Countersink Angle: 100.0 degrees Material: Titanium alloy uns r54520 Material Specification: Ams4967 mfr ref single material response
Grip Length: Between 0.557 inches and 0.567 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 95000 pounds per square inch Thread Size: 0.250 inches Shear Strength: 10490 double pounds per square inch Countersink Angle: 100.0 degrees Material: Titanium alloy uns r54520 Material Specification: Ams4967 mfr ref single material response
Between 0.557 inches and 0.567 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 95000 pounds per square inch Thread Size: 0.250 inches Shear Strength: 10490 double pounds per square inch Countersink Angle: 100.0 degrees Material: Titanium alloy uns r54520 Material Specification: Ams4967 mfr ref single material response
Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 95000 pounds per square inch Thread Size: 0.250 inches Shear Strength: 10490 double pounds per square inch Countersink Angle: 100.0 degrees Material: Titanium alloy uns r54520 Material Specification: Ams4967 mfr ref single material response
Min. Tensile Strength (psi): 95000 pounds per square inch Thread Size: 0.250 inches Shear Strength: 10490 double pounds per square inch Countersink Angle: 100.0 degrees Material: Titanium alloy uns r54520 Material Specification: Ams4967 mfr ref single material response
Min. Tensile Strength (psi): 95000 pounds per square inch Thread Size: 0.250 inches Shear Strength: 10490 double pounds per square inch Countersink Angle: 100.0 degrees Material: Titanium alloy uns r54520 Material Specification: Ams4967 mfr ref single material response
95000 pounds per square inch Thread Size: 0.250 inches Shear Strength: 10490 double pounds per square inch Countersink Angle: 100.0 degrees Material: Titanium alloy uns r54520 Material Specification: Ams4967 mfr ref single material response
Thread Size: 0.250 inches Shear Strength: 10490 double pounds per square inch Countersink Angle: 100.0 degrees Material: Titanium alloy uns r54520 Material Specification: Ams4967 mfr ref single material response
0.250 inches Shear Strength: 10490 double pounds per square inch Countersink Angle: 100.0 degrees Material: Titanium alloy uns r54520 Material Specification: Ams4967 mfr ref single material response
Shear Strength: 10490 double pounds per square inch Countersink Angle: 100.0 degrees Material: Titanium alloy uns r54520 Material Specification: Ams4967 mfr ref single material response
10490 double pounds per square inch Countersink Angle: 100.0 degrees Material: Titanium alloy uns r54520 Material Specification: Ams4967 mfr ref single material response
Countersink Angle: 100.0 degrees Material: Titanium alloy uns r54520 Material Specification: Ams4967 mfr ref single material response
100.0 degrees Material: Titanium alloy uns r54520 Material Specification: Ams4967 mfr ref single material response
Material: Titanium alloy uns r54520 Material Specification: Ams4967 mfr ref single material response
Titanium alloy uns r54520 Material Specification: Ams4967 mfr ref single material response
Material Specification: Ams4967 mfr ref single material response
Ams4967 mfr ref single material response
·
Thread Series Designator:
Unjf
Specification Data:
73197-hl111vf-8-9 manufacturers standard
Shelf Life:
N/a

NSN 5320-01-321-7826

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0