# NSN 5320-01-321-8625

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-321-8625

| Head Style |  |
|------------|--|

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

# **Shank Diameter:**

Between 0.3725 inches and 0.3745 inches

# **Shank Style:**

Threaded self-plugging shank w/sleeve

# **Head Major Diameter:**

Between 0.752 inches and 0.762 inches

# **Expansion Device:**

Threaded mandrel

# **Grip Length:**

Between 0.720 inches and 0.781 inches

# **Hardness Rating:**

39.0 rockwell c nut and 43.0 rockwell c nut

# **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### Material:

Steel comp 304 sleeve or steel comp 303f sleeve or steel comp 303 sleeve

# **Surface Treatment:**

Cadmium sleeve and passivate sleeve

# **Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response nut

# **Specification Data:**

80205-nas1670 professional/industrial association standard

# Shelf Life:

N/a

# **Unit Of Measure:**

--

# Demilitarization:

No

# Fiig:

A040a0