NSN 5320-01-321-8629

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-321-8629 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.802 inches and 1.822 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3110 inches and 0.3120 inches **Shank Style: Head Major Diameter:** Between 0.469 inches and 0.474 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 1.307 inches and 1.317 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.312 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp 431 **Material Specification:** Ams 5628 assn standard single material response or mil-s-18732 military specification single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-321-8629

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.