NSN 5320-01-321-9747

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-321-9747

| Fastener Length: |
|---|
| 1.092 inches |
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.162 inches and 0.164 inches |
| Shank Style: |
| Self-plugging mechanically locked stem |
| Head Major Diameter: |
| 0.333 inches |
| Expansion Device: |
| Serrated stem-type w |
| Grip Length: |
| Between 0.906 inches and 0.970 inches |
| Min. Tensile Strength (psi): |
| 112000 pounds per square inch |
| Hardness Rating: |
| 48.0 rockwell c stem and 53.0 rockwell c stem |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Special Features: |
| Single action fastener without frangible type of locking collar or locking collar cap |
| Material: |
| Steel comp 8740 stem |
| Material Specification: |
| Astm a331 assn standard single material response stem |
| Surface Treatment: |
| Cadmium stem |
| Surface Treatment Specification: |
| Qq-p-416, type 2, cl 2 federal specification all treatment responses mechanical lock |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |
| |