NSN 5320-01-322-2612

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-322-2612 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.740 inches and 0.760 inches **Head Style:** Err-090 **Head Height:** Between 0.037 inches and 0.047 inches Width Between Flats: Between 0.0791 inches and 0.0801 inches **Shank Diameter:** Between 0.1625 inches and 0.1635 inches **Shank Style: Head Major Diameter:** Between 0.242 inches and 0.262 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.433 inches and 0.443 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches **Shear Strength:** 125000 single pounds per square inch Material: Steel comp 431 **Material Specification:** Ams 5628 assn standard single material response or mil-s-18732 military specification single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjc Shelf Life: N/a

--

Unit Of Measure:

NSN 5320-01-322-2612

Pin-rivet - Page 2 of 2



Demi			

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.