## NSN 5320-01-322-3184

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-322-3184

Thread Class:

Thread Class:
3b
Thread Direction:
Right-hand
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.387 inches and 0.390 inches
Shank Style:
Blind rivet, nut and bolt (assembly)
Head Major Diameter:
Between 0.445 inches and 0.450 inches
Expansion Device:
Threaded mandrel
Grip Length:
Between 0.157 inches and 0.218 inches
Thready Qty Per Inch (tpi):
28
Thread Size:
0.250 inches
Countersink Angle:
Between 98.0 degrees and 102.0 degrees
Special Features:
Furnished without bolt
Heat Treatment:
Annealed sleeve
Material:
Steel comp 304 sleeve or steel comp 305 sleeve
Material Specification:
Qq-s-763, cond a federal specification 1st material response sleeve
Surface Treatment:
Cadmium expander and chromate expander
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response expander
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5320-01-322-3184

Blind Rivet - Page 2 of 2



Fiig:

A040a0

Mil-std (military Standard):

Mil-s-18732 spec.