NSN 5320-01-322-5334

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-322-5334 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.552 inches and 0.572 inches **Head Style:** Err-090 **Head Height:** Between 0.085 inches and 0.095 inches Width Between Flats: Between 0.079 inches and 0.080 inches **Shank Diameter:** Between 0.163 inches and 0.164 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.240 inches and 0.260 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.245 inches and 0.255 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.164 inches **Special Features:** Appl data f100pw0229 engine: head is flat on two sides Material: Nickel alloy **Material Specification:** Ams 5708 ni alloy federal specification single material response **Surface Treatment: Passivate Thread Series Designator:** Unjc Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-322-5334

Pin-rivet - Page 2 of 2



| _ | | •• | • • | | | | |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш | 112 | rız | 211 | n | ٠. |
| | | | | | | | |

No

Fiig:

A528u0