## NSN 5320-01-322-6595

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-322-6595



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

### Fastener Length:

Between 2.223 inches and 2.243 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.078 inches and 0.088 inches

#### Width Between Flats:

Between 0.1582 inches and 0.1617 inches

#### Shank Diameter:

Between 0.3735 inches and 0.3745 inches

#### Shank Style:

#### Head Major Diameter:

Between 0.565 inches and 0.600 inches

### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

### Grip Length:

Between 1.683 inches and 1.693 inches

#### Thready Qty Per Inch (tpi):

24

#### **Thread Size:**

0.375 inches

### Shear Strength:

125000 single pounds per square inch

#### Material:

Steel comp 431

#### **Material Specification:**

Ams 5628 assn standard single material response or mil-s-18732 military specification single material response

#### Surface Treatment:

Cadmium and chromate

#### Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

## **Thread Series Designator:**

Unjf

Shelf Life:

N/a

## Unit Of Measure:

--

# NSN 5320-01-322-6595

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.

