## NSN 5320-01-323-5602

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-323-5602 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.010 inches and 1.030 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.158 inches and 0.162 inches **Shank Diameter:** Between 0.380 inches and 0.381 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.555 inches and 0.560 inches Lubrication: Solid film and cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.375 inches and 0.385 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.375 inches **Shear Strength:** 132000 single pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** Lf-31-35-8, solid film lubricant with light blue identification on top of head Material: Steel **Material Specification:** M+35n sps-m-573, cagec 56878 mfr ref single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 5320-01-323-5602

Pin-rivet - Page 2 of 2



Fiig:

A528u0