

View Online at <https://aerobasegroup.com/nsn/5320-01-323-5602>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.010 inches and 1.030 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.158 inches and 0.162 inches

**Shank Diameter:**

Between 0.380 inches and 0.381 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.555 inches and 0.560 inches

**Lubrication:**

Solid film and cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

Between 0.375 inches and 0.385 inches

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.375 inches

**Shear Strength:**

132000 single pounds per square inch

**Countersink Angle:**

100.0 degrees

**Special Features:**

Lf-31-35-8, solid film lubricant with light blue identification on top of head

**Material:**

Steel

**Material Specification:**

M+35n sps-m-573, caged 56878 mfr ref single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0