# NSN 5320-01-323-6158

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-323-6158



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 0.677 inches and 0.697 inches

### Head Style:

Flush countersunk

### Width Between Flats:

Between 0.0635 inches and 0.0645 inches

#### Shank Diameter:

Between 0.1625 inches and 0.1635 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.2564 inches and 0.2612 inches

Lubrication:

Solid film

#### **End Application:**

Aircraft, b-1b

# Grip Length:

Between 0.370 inches and 0.380 inches

### Thready Qty Per Inch (tpi):

32

### **Thread Size:**

0.164 inches

#### Shear Strength:

125000 single pounds per square inch

### Countersink Angle:

100.0 degrees

Material:

Steel comp xm-13

### Material Specification:

Ams 5629 assn standard single material response

#### **Thread Series Designator:**

Unjc

# Shelf Life:

N/a

## Unit Of Measure:

---

# Demilitarization:

No

# NSN 5320-01-323-6158

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

