# NSN 5320-01-323-8475

Pin-rivet - Page 1 of 2





# **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

0.899 inches

## Head Style:

Err-090

#### **Head Height:**

Between 0.037 inches and 0.047 inches

#### Shank Diameter:

Between 0.1625 inches and 0.1635 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.242 inches and 0.262 inches

#### Lubrication:

Cetyl alcohol

# Grip Length:

0.625 inches

# Thready Qty Per Inch (tpi):

32

#### Thread Size:

0.164 inches

## Shear Strength:

108000 single pounds per square inch

#### Material:

Steel comp 4340 or steel comp 8740

#### Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response

#### Surface Treatment:

Cadmium and chromate

#### Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

#### Thread Series Designator:

Unjc

# Shelf Life:

N/a

#### Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-01-323-8475

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

Mil-std (military Standard):

Mil-s-5000 spec.

