# NSN 5320-01-323-8476

Pin-rivet - Page 1 of 2





## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

1.280 inches

## Head Style:

Err-090

#### **Head Height:**

Between 0.045 inches and 0.055 inches

#### Shank Diameter:

Between 0.1885 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.295 inches and 0.315 inches

#### Lubrication:

Cetyl alcohol

# Grip Length:

1.000 inches

## Thready Qty Per Inch (tpi):

32

## Thread Size:

0.190 inches

#### Shear Strength:

108000 single pounds per square inch

#### Material:

Steel comp 4340 or steel comp 8740

#### Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response

#### Surface Treatment:

Cadmium and chromate

#### Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

## Thread Series Designator:

Unjf

# Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-01-323-8476

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

Mil-std (military Standard):

Mil-s-5000 spec.

