NSN 5320-01-324-0154

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-324-0154

Thread	Class:

3a

Thread Direction:

Right-hand

Fastener Length:

0.391 inches

Head Style:

Err-090

Head Height:

Between 0.032 inches and 0.042 inches

Shank Diameter:

Between 0.1365 inches and 0.1375 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.225 inches and 0.240 inches

Lubrication:

Cetyl alcohol

Grip Length:

0.156 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Shear Strength:

108000 single pounds per square inch

Special Features:

32 micro inches on the shank

Material:

Steel comp e4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

NSN 5320-01-324-0154

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.

