## NSN 5320-01-324-0162

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-324-0162

## **Thread Class:** 3a **Thread Direction: Right-hand** Fastener Length: 0.836 inches **Head Style:** Err-090 **Head Height:** Between 0.037 inches and 0.047 inches Shank Diameter: Between 0.1625 inches and 0.1635 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.242 inches and 0.262 inches Lubrication: Cetyl alcohol Grip Length: 0.562 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches Shear Strength: 108000 single pounds per square inch Material: Steel comp 4340 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response Surface Treatment: Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjc Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No

## NSN 5320-01-324-0162

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

Mil-std (military Standard):

Mil-s-5000 spec.

