NSN 5320-01-324-4229

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-324-4229

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Fastener Length: |
| Between 1.271 inches and 1.296 inches |
| Head Style: |
| Err-090 |
| Head Height: |
| Between 0.082 inches and 0.094 inches |
| Shank Diameter: |
| 0.4068 inches |
| Head Major Diameter: |
| Between 0.582 inches and 0.596 inches |
| Tip Diameter: |
| 0.3906 inches |
| Lubrication: |
| Cetyl alcohol |
| Grip Length: |
| Between 0.865 inches and 0.880 inches |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 180000 pounds per square inch |
| Thread Size: |
| 0.375 inches |
| Shear Strength: |
| 108000 single pounds per square inch |
| Material: |
| Steel comp 8740 or steel comp e4340 |
| Material Specification: |
| Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416, type 2, cl 2 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 80205-nas1728 professional/industrial association standard |
| Shelf Life: |

N/a

NSN 5320-01-324-4229

Pin-rivet - Page 2 of 2



| | • - | | |
|----|-----|------|----------|
| In | ıŧ | ()t | Measure: |
| | | | |

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.