NSN 5320-01-324-7441

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-324-7441 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Natural **Fastener Length:** Between 1.490 inches and 1.510 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0635 inches and 0.0645 inches **Shank Diameter:** Between 0.1625 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.2874 inches and 0.2922 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 1.183 inches and 1.193 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches **Countersink Angle:** 100.0 degrees **Heat Treatment:** T-6 solution heat treated Material: Aluminum alloy 7075 **Material Specification:** Qq-a-225/9 federal specification single material response or qq-a-430 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Thread Series Designator:** Unjc

N/a

Shelf Life:

NSN 5320-01-324-7441

Pin-rivet - Page 2 of 2



ι	Jn	it	Of	Measure:	•

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-a-8625 spec.