NSN 5320-01-325-2029

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-325-2029

Thread Class:

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
0.468 inches
Head Style:
Err-090
Head Height:
Between 0.045 inches and 0.055 inches
Shank Diameter:
Between 0.1885 inches and 0.1895 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.295 inches and 0.315 inches
Lubrication:
Cetyl alcohol
Grip Length:
0.188 inches
Thready Qty Per Inch (tpi):
32
Thread Size:
0.190 inches
Shear Strength:
108000 single pounds per square inch
Special Features:
32 micro inches on shank
Material:
Steel comp 4340 or steel comp 8740
Material Specification:
Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

--

Unit Of Measure:

NSN 5320-01-325-2029

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.