## NSN 5320-01-326-7636

Pin-rivet - Page 1 of 2





### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.885 inches and 1.905 inches

## Head Style:

Err-090

#### Head Height:

Between 0.059 inches and 0.069 inches

## Width Between Flats:

Between 0.0947 inches and 0.0967 inches

### Shank Diameter:

Between 0.2490 inches and 0.2495 inches

### Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

Between 0.387 inches and 0.412 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

Between 1.495 inches and 1.505 inches

## Thready Qty Per Inch (tpi):

28

## Thread Size:

0.250 inches

## Shear Strength:

95000 single pounds per square inch

## **Special Features:**

Grit blast top of heads

## Material:

Titanium alloy uns r56400

## Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

## Thread Series Designator:

Unjf

## Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

# NSN 5320-01-326-7636

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

