NSN 5320-01-326-8005

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-326-8005

Fastener Length:
Between 1.740 inches and 1.760 inches
Head Style:
Countersunk w/ reverse chamfer
Head Height:
0.051 inches
Shank Diameter:
Between 0.186 inches and 0.189 inches
Shank Style:
Straight
Head Major Diameter:
0.258 inches
Min. Tensile Strength (psi):
68000 pounds per square inch
Minimum Yield Strength:
58000 pounds per square inch
Shear Strength:
41000 single pounds per square inch
Countersink Angle:
Between 118.5 degrees and 121.5 degrees
Heat Treatment:
T-73 solution heat treated
T-73 solution heat treated Material:
Material:
Material: Aluminum alloy
Material: Aluminum alloy Material Specification:
Material: Aluminum alloy Material Specification: Qq-a-430, alloy 7050 federal specification single material response
Material: Aluminum alloy Material Specification: Qq-a-430, alloy 7050 federal specification single material response Surface Treatment:
Material: Aluminum alloy Material Specification: Qq-a-430, alloy 7050 federal specification single material response Surface Treatment: Anodize
Material: Aluminum alloy Material Specification: Qq-a-430, alloy 7050 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification:
Material: Aluminum alloy Material Specification: Qq-a-430, alloy 7050 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2, cl 1 military specification single treatment response
Material: Aluminum alloy Material Specification: Qq-a-430, alloy 7050 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2, cl 1 military specification single treatment response Shelf Life:
Material: Aluminum alloy Material Specification: Qq-a-430, alloy 7050 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2, cl 1 military specification single treatment response Shelf Life: N/a
Material: Aluminum alloy Material Specification: Qq-a-430, alloy 7050 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2, cl 1 military specification single treatment response Shelf Life: N/a
Material: Aluminum alloy Material Specification: Qq-a-430, alloy 7050 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2, cl 1 military specification single treatment response Shelf Life: N/a Unit Of Measure:
Material: Aluminum alloy Material Specification: Qq-a-430, alloy 7050 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2, cl 1 military specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization:
Material: Aluminum alloy Material Specification: Qq-a-430, alloy 7050 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2, cl 1 military specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No
Material: Aluminum alloy Material Specification: Qq-a-430, alloy 7050 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2, cl 1 military specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: