
# NSN 5320-01-327-0398

Pin-rivet - Page 1 of 2





# **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

0.945 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.068 inches and 0.078 inches

## Shank Diameter:

Between 0.3110 inches and 0.3120 inches

#### Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

Between 0.475 inches and 0.505 inches

#### Lubrication:

Cetyl alcohol

# End Application:

C-5b aircraft

## Grip Length:

0.531 inches

## Thready Qty Per Inch (tpi):

24

## **Thread Size:**

0.3125 inches

## Shear Strength:

108000 single pounds per square inch

## Material:

Steel comp e4340 or steel comp 8740

## **Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response

#### Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

## **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-01-327-0398

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.

