# NSN 5320-01-327-0403

Pin-rivet - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5320-01-327-0403



## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 0.690 inches and 0.710 inches

## Head Style:

Flush countersunk

## Width Between Flats:

Between 0.0791 inches and 0.0806 inches

# Shank Diameter:

Between 0.2177 inches and 0.2182 inches

## Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

Between 0.3253 inches and 0.3303 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

# Grip Length:

Between 0.370 inches and 0.380 inches

# Thready Qty Per Inch (tpi):

32

# **Thread Size:**

0.190 inches

# Shear Strength:

95000 single pounds per square inch

# **Countersink Angle:**

100.0 degrees

Material:

Titanium alloy uns r56400

# **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

## **Thread Series Designator:**

Unjf

#### Shelf Life:

N/a

# Unit Of Measure:

---

## **Demilitarization:**

No

# Fiig:

A528u0