

View Online at <https://aerobasegroup.com/nsn/5320-01-327-5823>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.178 inches and 1.198 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.1270 inches and 0.1295 inches

**Shank Diameter:**

Between 0.3115 inches and 0.3120 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.5951 inches and 0.6037 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**End Application:**

W/s: aircraft, b-2 bomber (atb)

**Grip Length:**

Between 0.683 inches and 0.693 inches

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.312 inches

**Shear Strength:**

96000 single pounds per square inch

**Countersink Angle:**

130.0 degrees

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0