# NSN 5320-01-327-6682

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-327-6682



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 0.565 inches and 0.585 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.045 inches and 0.055 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.2177 inches and 0.2182 inches

#### Shank Style:

Pin-rivet, straight, threaded

### Head Major Diameter:

Between 0.295 inches and 0.315 inches

# Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

# Grip Length:

Between 0.245 inches and 0.255 inches

#### Thready Qty Per Inch (tpi):

32

#### **Thread Size:**

0.190 inches

# Shear Strength:

95000 single pounds per square inch

#### Countersink Angle:

100.0 degrees

#### Material:

Titanium alloy uns r56400

#### Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

# NSN 5320-01-327-6682

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

