# NSN 5320-01-327-9117

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-327-9117

### Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

## Shank Diameter:

Between 0.2020 inches and 0.2025 inches

## Shank Style:

Threaded self-plugging shank w/sleeve

## Head Major Diameter:

0.375 inches

#### **Expansion Device:**

Threaded stem

#### Lubrication:

Dry film or cetyl alcohol or paraffin wax

#### Grip Length:

Between 0.407 inches and 0.469 inches

#### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### **Special Features:**

Powder blast top surface of head, remainder of body optional

#### Material:

Titanium alloy uns r56400 stem

### Material Specification:

Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 2nd material response sleeve or ams 5641 assn

standard 3rd material response sleeve

### Surface Treatment:

Passivate sleeve

#### **Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response sleeve

### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A040a0