# NSN 5320-01-327-9122

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-327-9122



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 0.490 inches and 0.510 inches

### Head Style:

Err-090

#### **Head Height:**

Between 0.055 inches and 0.065 inches

### Shank Diameter:

Between 0.1630 inches and 0.1635 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

Between 0.183 inches and 0.193 inches

### Width Across Flats:

Between 0.242 inches and 0.251 inches

# Thready Qty Per Inch (tpi):

32

## Min. Tensile Strength (psi):

160000 pounds per square inch

## Thread Size:

0.164 inches

### **Special Features:**

Protrudng special flat or hex head

### Material:

Nickel alloy

### **Material Specification:**

Ams 5708 assn standard single material response

### Surface Treatment:

Passivate

## Surface Treatment Specification:

Spec 258, cagec 73197 mfr ref single treatment response

# **Thread Series Designator:**

Unjc

# Shelf Life:

N/a

### Unit Of Measure:

---

# NSN 5320-01-327-9122

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

