

View Online at <https://aerobasegroup.com/nsn/5320-01-327-9124>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.948 inches and 1.968 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.2520 inches and 0.2555 inches

Shank Diameter:

Between 0.5610 inches and 0.5615 inches

Shank Style:

Pin-rievet, straight, threaded

Head Major Diameter:

Between 1.1337 inches and 1.1408 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 1.183 inches and 1.193 inches

Thready Qty Per Inch (tpi):

18

Thread Size:

0.5625 inches

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

Grit blast top of heads; 0-ring, synthetic rubber per mil-r-6855, class 1 2, and 3, and mil-r-3065, class sb612e, temperature range-70 degrees to 225 degrees f

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0