# NSN 5320-01-327-9129

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-327-9129



## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 0.740 inches and 0.760 inches

#### Head Style:

Flush countersunk

## Width Between Flats:

Between 0.0791 inches and 0.0801 inches

# Shank Diameter:

Between 0.1630 inches and 0.1635 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.2564 inches and 0.2612 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

Between 0.433 inches and 0.443 inches

# Thready Qty Per Inch (tpi):

32

#### **Thread Size:**

0.164 inches

#### Shear Strength:

95000 single pounds per square inch

#### **Countersink Angle:**

100.0 degrees

#### **Special Features:**

Grit blast top of heads

#### Material:

Titanium alloy uns r56400

#### Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Thread Series Designator:

Unjc

# Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

# NSN 5320-01-327-9129

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

