NSN 5320-01-327-9130

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-327-9130



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.677 inches and 0.697 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0791 inches and 0.0801 inches

Shank Diameter:

Between 0.1630 inches and 0.1635 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.2564 inches and 0.2612 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.370 inches and 0.380 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.164 inches

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

Grit blast top of heads

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5320-01-327-9130

Pin-rivet - Page 2 of 2

Fiig: A528u0

