NSN 5320-01-328-1574

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-328-1574 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** Between 1.010 inches and 1.030 inches **Head Style:** Err-090 **Head Height:** Between 0.080 inches and 0.090 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style: Head Major Diameter:** Between 0.415 inches and 0.440 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.620 inches and 0.630 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 96000 single pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5320-01-328-1574

Pin-rivet - Page 2 of 2



Fiig:

A528u0