

View Online at <https://aerobasegroup.com/nsn/5320-01-328-4570>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.819 inches and 0.839 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0635 inches and 0.0645 inches

Shank Diameter:

Between 0.1365 inches and 0.1375 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.2171 inches and 0.2219 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 0.589 inches and 0.599 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.