NSN 5320-01-328-6103

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-328-6103



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.6145 inches and 0.6345 inches

Head Style:

Err-090

Head Height:

Between 0.037 inches and 0.047 inches

Width Between Flats:

Between 0.0791 inches and 0.0801 inches

Shank Diameter:

Between 0.1625 inches and 0.1635 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.242 inches and 0.262 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.3075 inches and 0.3175 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.164 inches

Shear Strength:

95000 single pounds per square inch

Special Features:

Grit blast top of heads

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5320-01-328-6103

Pin-rivet - Page 2 of 2

Fiig: A528u0

